



S2.2 Trolley

► General

- Throw 25m
- Aerodynamic composite lightweight cone
- Hot dipped galvanized structure
- Low noise high efficiency fan
- Adjustable angle of throw -10° to 50°
- Integrated water filter system

► Water specifications

- A constant inlet press. of 1,5 bar with the rated flow
- HP Pump
- Waterbox filtersystem with flushfunction
- 1/2" BSP male fitting
- Stainless steel nozzling
- HP nozzles
- Last chance filter before nozzle
- Droplet size spectrum vary from 30 to 50 micron
- Waterflow 400l/h

► Electrical specifications

- Voltage 3x400V 50Hz
- Fan (kw) 2.2
- Pump (kw) 1.5
- Rot. (kw) NA
- IP66 steel cabinet

► Options

- Bigger boosterpump(s)
- Pressure detection incl.
- Water cut off valve incl.
- Remote control
- Dosage pump
- Horizontal oscillation
- 3 x 480V 60Hz
- 1 x 230V

► Dimensions and weight

- Length 1350 mm
- Width 1100 mm
- Height 1550 mm
- Weight 210 kg

Spraystream

Standard machines



The Spraystream S2.2 Trolley is a dust suppression machine that generates a consistent stream of microdroplets to capture airborne dust particles and prevent fugitive dust's escape. This misting cannon is mainly used for dust- and odour suppression: **static or mobile, in- or outdoor, separate or in combination** with other misting cannons. The misting can be adjusted to the needs of the customer. This Spraystream S2.2 Trolley is also available without a trolley and in mono-phase.

