

Ceiling Grinder Frame



Flex Ceiling Grinder Frame, a mobile workstation for enabling sustained use without any effect of the machine weight. This unit requires significantly less user effort (reduced fatigue and strain), compared to standard ceiling grinding requirements.

The mobile workstation has a durable frame for demanding applications on construction sites. The unit can be quickly assembled, changed and disassembled without any tools thanks to the quick-release clamps. The working height can also be adjusted without tools thanks to a double clamp on the lifting rod.

The ceiling grinder frame is equipped with a robust folding mechanism for easy transport. Equipped with soft grip handle, hose clip and cable holder for the 7.5 m rubber cable.

Large rubber wheels ensure optimal stability and manoeuvrability on construction sites. Additional covers on the wheel hubs provide protection against damage to walls.

Two power outlets provide the connection for power tools with 230 V/CEE.

Tilting tool fixture (90° in both directions) including pivot joint for optimum ease of movement, adaptation to ceilings and walls and for a perfect finish on slanted surfaces. The plastic sliding bush ensures smooth running as well as precise guiding over the surface.

Specifications:	
Max. working height	3400 mm
Device connection	2 x 230 V CEE
Cable length	7.5 m
Dimensions (W, L, H) mm	2630 x 660 x 1680
Weight	31.5 kg

We recommend using this product in conjunction with our DL3000 Grinding Vacuum.



Ceiling Grinder



Ceiling Grinder with electronic control for constant speed, soft-start and overload protection.

Using a unique telescopic system, the Flex Ceiling Grinder adapts to your required reach. Length adjustable from 1330 mm - 1730 mm, with easy telescopic adjustment.

Ergonomic design with different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance.

Vacuum dust extraction: reduces airborne dust and minimises disc wear.

The dust extraction system has a metal ring on the guard and a flexible suction hose from the scouring head to the guide tube to optimise dust extraction.

Connection for the vacuum is at the rear of the telescopic tube.

Specifications:	
Disc	125 mm
Speed without load	8000 rpm
Power input	1010 watt
Power output	600 watt
Tool fixture	28 mm
Dimensions in mm	1330 - 1730
Weight	5.50 kg

We recommend using this product in conjunction with our DL3000 Grinding Vacuum.

